


Model No	726CRK-P IP Camera
Photo	
Pixel	2MP
Processor	MSC313E
Image sensor	1/2.7" SOI F22
Lens	3.6MM
OS	Linux operating system
Scanning system	PAL / NTSC
Compression	H.264 / H.265
Stream	32 Kbps~ 8Mbps
video output	main stream:1920*1080 Substream:640*480
Frame rate	1-20fps adjustable
Audio input	not support
Audio output	not support
Day / Night	Built-in IR-CUT dual filter
IR LEDs	4pcs array infrared light
Minimum illumination	0.1Lux/F1.2(colorful) / 0.01Lux/F1.2(Black & white)
wide dynamic range	Support DWD,Backlight installation
Noise reduction	3D DNR
Video saving	NVR、 PC
Alarm events	Motion detection, occlusion alarm, video loss, network cable disconnection, IP address conflict
Safety protection	Password protection, Administrator privilege settings
CCTV Protocol	ONVIF / Hikvision / Dahua / XM Private Protocol
Network protocol	HTTP/RTSP/DHCP network protocol and so on
Storage	N/A
Waterproof level	IP66
Cover material	metal
IR distance	0-25M
Storage occupation	10G/day (H.265)
Language	Support Simplified Chinese, English
APP	iOS、 Android
Ethernet port	RJ45 X 1, 10M/100M
Cable	DC12V+RJ45
Cloud service	Danale
Lightning protection	Power Supply 2.3KV LAN Port 6KV
Power Supply	DC12V
Power consumption	less than 5W
Working Temperature	-25°C - 70°C
Dimension	198*74*60
Net Weight	0.5kg